

Landing Leg



The AL-KO Landing Leg is the latest addition to AL-KO's extensive range of quality trailer components.

Ideal for stabilising plant trailers, camper trailers, 5 wheeler caravans and agricultural equipment, the AL-KO Landing Leg is a necessary inclusion to the toolkit of the commercial contractor, farmer and camping enthusiast alike.

All bases are covered with the AL-KO range of Landing Legs, with static loads ranging from 1,300 to 4,500kg. The standard plant trailer right up to a fully loaded water tank is easily stabilised into position with the side wind operation.

Flexibility is a major feature of the AL-KO Landing Leg range. The customer can choose to include or exclude tube mounting kits. An AL-KO Landing Leg can also be fitted to another brands existing mounting kit.

The AL-KO Landing Leg is your ideal choice when looking to safely and efficiently stabilise your trailer, camper, 5 wheeler caravan or agricultural machinery.

Features & Benefits

- Extensive range, for static loads from 1,300 to 4,500kg
- Zinc plated for added corrosion resistance
- Bottom plate drilled to allow drainage and therefore prevents corrosion
- Drop down leg on select models providing added functionality
- Available with or without mounting kit for added flexibility
- Can be fitted to another brands existing mounting kit
- All side wind for speedy operation
- 4,500kg unit has one handle wind point to allow a rod to connect two legs and therefore wind two legs at once
- Backed by the AL-KO 12 month warranty for peace of mind









Further information can be obtained by contacting AL-KO on 1800 035 603 or by visiting:

www.alko.com.au

AL-KO International Pty Ltd (ABN 96 003 066 813)

VIC: 67 Nathan Road, Dandenong South, 3175 Phone (03) 9767 3700 Fax (03) 9792 0877
NSW: 14 Toohey Road, Wetherill Park, 2164 Phone (02) 8784 9400 Fax (02) 9725 4557
QLD: 62 Parramatta Road, Underwood, 4119 Phone (07) 3386 6300 Fax (07) 3808 1719

The Range

Part No.	Outer Tube mm ²	Tube Mount Fitted	Unitary Weight kg	Static Load Capacity kg	Surface Finish	Qty Per Carton	Screw Stroke mm	A1 mm	A2 mm	B mm	C mm	D mm	
622057	Round Ø 57.5	Yes	6.7	1,300	Zinc Plated	2	400	550	900	400	167	118	
622057L	Round Ø 57.5	Yes	9.1	1,300	Zinc Plated	2	380	1060	1440	910	167	118	
622070	Square 70.0 with drop down leg	No	11.8	1,500	Zinc Plated	2	680	595	1275	-	167	118	
622071	Square 70.0	No	9.9	2,000	Zinc Plated	2	360	580	940	-	167	118	
622071WTM	Square 70.0	Yes	10.4	2,000	Zinc Plated	2	360	580	940	430	167	118	
622110	Square 110.0	No	32.9	4,500	Zinc Plated	1	585	690	1275	-	326	250	
622000	Chassis mount & tube bracket kit				Zinc Plated	1			-				